

View Online at <https://aerobasegroup.com/nsn/5935-00-321-7969>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external/internal coupling

Overall Length:

1.156 inches

Overall Diameter:

0.563 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable single mating end all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet latch and externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic fluorocarbon all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.