Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-321-8290

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.172 inches and 1.234 inches

Overall Height:

Between 1.610 inches and 1.640 inches

Overall Width:

Between 1.610 inches and 1.640 inches

Environmental Protection:

Salt water resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.270 inches and 1.280 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.270 inches and 1.280 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

37p single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic silicone mineral filled single mating end

Terminal Type:

Crimp single mating end single contact grouping



Shell Material: Aluminum **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 37 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.037 gold grains, troy and 0.037 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0