NSN 5935-00-325-5164

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-325-5164

Body Style: Straight shape threaded **Overall Length:** 0.696 inches **Overall Diameter:** 0.969 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Distance From Mounting Shoulder To Front Face:** 0.419 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-19 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 30.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Metal ferrous single mating end single contact grouping **Contact Surface Treatment:** Tin single mating end single contact grouping **Terminal Type:** Wire loop single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** Tin **Included Contact Quantity:**

19 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-00-325-5164

Electrical Receptacle Connector - Page 2 of 2



Solder flange mounted and hermetically sealed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0