## NSN 5935-00-325-6875

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-325-6875 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 4.295 inches and 4.305 inches **Overall Height:** 0.828 inches **Distance Between Mounting Facility Centers:** Between 3.995 inches and 4.005 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.250 inches **Thread Size:** 0.112 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-750 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:** 

37 single mating end single contact grouping

## NSN 5935-00-325-6875

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0