## NSN 5935-00-326-0580

Thread Class: 2a and 2b

**Body Style:** 

Overall Length: 1.563 inches Overall Height:

**Thread Direction:** 

Right-hand and right-hand

Hood, top opening w/clamp

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-326-0580

1.844 inches
Overall Width:
0.500 inches
Cable Entrance Diameter:
0.656 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Shell Type: Hood, top opening
Hood, top opening
Hood, top opening  Connector Locking Method:
Hood, top opening  Connector Locking Method:  Jackscrew-socket
Hood, top opening  Connector Locking Method:  Jackscrew-socket  Connector Cable Strain Relief Method:
Hood, top opening  Connector Locking Method:  Jackscrew-socket  Connector Cable Strain Relief Method:  Cable clamp
Hood, top opening  Connector Locking Method:  Jackscrew-socket  Connector Cable Strain Relief Method:  Cable clamp  Thread Size:
Hood, top opening  Connector Locking Method:  Jackscrew-socket  Connector Cable Strain Relief Method:  Cable clamp  Thread Size:  0.138 inches and 0.138 inches
Hood, top opening  Connector Locking Method:  Jackscrew-socket  Connector Cable Strain Relief Method:  Cable clamp  Thread Size:  0.138 inches and 0.138 inches  Terminal Location:
Hood, top opening  Connector Locking Method:  Jackscrew-socket  Connector Cable Strain Relief Method:  Cable clamp  Thread Size:  0.138 inches and 0.138 inches  Terminal Location:  Back single mating end single contact grouping
Hood, top opening  Connector Locking Method:  Jackscrew-socket  Connector Cable Strain Relief Method:  Cable clamp  Thread Size:  0.138 inches and 0.138 inches  Terminal Location:  Back single mating end single contact grouping  Contact Material:
Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.138 inches and 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.138 inches and 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Thread Size: 0.138 inches and 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping

## **NSN 5935-00-326-0580**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Elongated cable entry 21/32 in. Lg by 3/8 in. W
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0