

View Online at <https://aerobasegroup.com/nsn/5935-00-328-0279>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape threaded

Overall Length:

1.060 inches

Overall Diameter:

0.630 inches

Distance From Mounting Shoulder To Front Face:

0.530 inches

Mounting Facility Thickness:

0.176 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet shell

Thread Size:

0.500 inches

Terminal Location:

Front single mating end single contact grouping

Contact Material:

Beryllium and copper single mating end single contact grouping

Terminal Type:

Female terminal connection single mating end single contact grouping

Contact Material Specification:

Mil-g-45204 military specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Special Features:

Panel mounted-mounting hole diameter 0.500 in.; panel thickness 0.520 in.; isolated ground; bnc bulkhead; mounting method-surface

Precious Material And Location:

Shell silver and contact gold

Precious Material:

Silver and gold

Supplementary Features:

Tarnish resistant surface

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.