

View Online at <https://aerobasegroup.com/nsn/5935-00-328-0279>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

1.060 inches

**Overall Diameter:**

0.630 inches

**Distance From Mounting Shoulder To Front Face:**

0.530 inches

**Mounting Facility Thickness:**

0.176 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet shell

**Thread Size:**

0.500 inches

**Terminal Location:**

Front single mating end single contact grouping

**Contact Material:**

Beryllium and copper single mating end single contact grouping

**Terminal Type:**

Female terminal connection single mating end single contact grouping

**Contact Material Specification:**

Mil-g-45204 military specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 single mating end single contact grouping

**Special Features:**

Panel mounted-mounting hole diameter 0.500 in.; panel thickness 0.520 in.; isolated ground; bnc bulkhead; mounting method-surface

**Precious Material And Location:**

Shell silver and contact gold

**Precious Material:**

Silver and gold

**Supplementary Features:**

Tarnish resistant surface

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.