

View Online at <https://aerobasegroup.com/nsn/5935-00-328-2763>

**Thread Pitch Diameters:**

+0.108/+0.125 inches

**Thread Direction:**

Left-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

2.016 inches

**Overall Diameter:**

3.031 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

57.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

270.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Thready Qty Per Inch (tpi):**

18 and 3

**Thread Size:**

2.113 inches and 2.500 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Included Contact Quantity:**

35 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.050 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Npt and special acme

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0