NSN 5935-00-328-2846

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-328-2846 **Thread Class:** 2b **Thread Pitch Diameters:** +0.125/+0.145 inches **Thread Direction:** Left-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 10.375 inches **Overall Diameter:** 3.563 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Cable Entrance Diameter:** Between 1.375 inches and 1.500 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 245.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1750.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 90.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi):

Thread Size:

3.000 inches

NSN 5935-00-328-2846Electrical Plug Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.025 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0