Electrical Plug Connector - Page 1 of 2

<u>AeroBase</u> Group

View Online at https://aerobasegroup.com/nsn/5935-00-328-3576

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, internal coupling	
Overall Length:	
0.766 inches	
Overall Diameter:	
1.156 inches	
Environmental Protection:	
Moisture resistant and vibration resistant and salt water resistant	
Threaded Device Type:	
Back shell	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
14-18 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Bayonet latch	
Thread Length:	
0.219 inches	
Thready Qty Per Inch (tpi):	
20	
Thread Size:	
0.791 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and silver single mating end single contact grouping	ng
Terminal Type:	
Crime single moting and single contact grouping	

Crimp single mating end single contact grouping

NSN 5935-00-328-3576

Electrical Plug Connector - Page 2 of 2



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

18 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.018 gold grains, troy and 0.018 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data: 81349-mil-c-38999 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.