Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-328-3736

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling Overall Length:
1.438 inches
Overall Diameter:
0.688 inches
Environmental Protection:
Weather resistant
Cable Entrance Diameter:
0.141 inches
Distance From Mounting Shoulder To Front Face:
0.675 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
100.0 and 210.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
28
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Triaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and body surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0