Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-328-3775

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.437 inches |
| Overall Diameter: |
| 0.687 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.675 inches |
| Threaded Device Type: |
| Mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Bnc single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Key, multiple key groove |
| Insert Position In Deg: |
| 110.0 and 230.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Connector Cable Strain Relief Method: |
| Compression nut |
| Thread Size: |
| 0.500 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and copper single mating end single |
| Insert Material: |
| Plastic tetrafluoroethylene single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |

contact grouping



| Shell Material: |
|--|
| Copper alloy |
| Shell Surface Treatment: |
| Silver |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Triaxial pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold and shell surface silver |
| Precious Material And Weight: |
| 0.005 gold grains, troy and 0.100 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |