

View Online at <https://aerobasegroup.com/nsn/5935-00-328-3798>

Thread Class:

Al

Body Style:

Thru-hole mount

Overall Length:

0.875 inches

Overall Diameter:

0.607 inches

Distance From Mounting Shoulder To Rear Face:

0.845 inches

Mounting Facility Thickness:

Between 0.063 inches and 0.125 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

20.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

28.0 single mating end single contact grouping

Shell Type:

Solid

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Cadmium single mating end single contact grouping

Insert Material:

Plastic polysulfone single mating end

Contact Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Screw single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0