Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-328-3958

### **Body Style:**

Straight shape, external coupling w/backshell

### **Overall Length:**

0.697 inches

# **Overall Height:**

1.703 inches

### **Overall Width:**

1.703 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.142 inches and 0.157 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

# Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

### Insert Position In Deg:

26.0

### Shell Type:

Solid

### **Connector Locking Method:**

Bayonet pin

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium and nickel



Included Contact Quantity:

29 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.029 gold grains, troy and 0.029 silver grains, troy

#### **Precious Material:**

Gold and silver

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-38999 government specification

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0