

View Online at <https://aerobasegroup.com/nsn/5935-00-328-4071>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

Between 1.615 inches and 1.635 inches

**Overall Height:**

Between 0.636 inches and 0.640 inches

**Overall Width:**

0.390 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

Between 1.405 inches and 1.411 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

50 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Thread Size:**

0.099 inches and 0.099 inches and 0.099 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 type 2, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 class 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

50 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.050 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.