NSN 5935-00-328-4086

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-328-4086

Body Style:

Straight shape threaded

Overall Length:

0.688 inches

Overall Diameter:

Between 1.021 inches and 1.042 inches

Environmental Protection:

Moisture resistant and hermetic

Distance From Mounting Shoulder To Front Face:

0.317 inches

Mating End Quantity:

Contact Position Arrangement Style:

14-15 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

600.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

850.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Glass single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Steel

Shell Surface Treatment:

Tin

NSN 5935-00-328-4086

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
14 single mating end 2nd contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Solder flange mounted
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0