NSN 5935-00-328-4277

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-328-4277

view Offilite at https://defobasegroup.com/histi/0500-00-020-4211
Body Style:
Straight shape
Overall Length:
1.869 inches
Overall Width:
0.275 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
1.594 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
100.0 single mating end single contact grouping
Polarization Method:
Mating end
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg military specification single material response single mating end
Included Contact Quantity:
45 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:

0.045 gold grains, troy

NSN 5935-00-328-4277

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: No

Mil-std (military Standard):

Mil-g-45204 spec.