

View Online at <https://aerobasegroup.com/nsn/5935-00-329-4982>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.090 inches

**Overall Diameter:**

0.875 inches

**Environmental Protection:**

Corrosion resistant and shock resistant and vibration resistant and hermetic

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14s-2 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

200.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.875 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Steel single mating end single contact grouping

**Contact Surface Treatment:**

Cadmium single mating end single contact grouping and tin single mating end single contact grouping

**Insert Material:**

Glass single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium and tin

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0