## NSN 5935-00-331-1416

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-331-1416

**Body Style:** 

Straight shape, external coupling w/strain relief

Diameter:

1.087 inches

**Environmental Protection:** 

Watertight

**Cable Entrance Diameter:** 

0.281 inches

**Mating End Quantity:** 

1

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

0.5 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:** 

60.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

85.0 single mating end all contact groupings

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet latch

**Connector Cable Strain Relief Method:** 

Cable clamp

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Tin single mating end all contact groupings

**Insert Material:** 

Plastic single mating end

**Terminal Type:** 

Solder well single mating end all contact groupings

**Shell Material:** 

Stainless steel

**Shell Surface Treatment:** 

Anodize

**Included Contact Quantity:** 

7 single mating end 2nd contact grouping

## NSN 5935-00-331-1416

Electrical Plug Connector - Page 2 of 2



| ncluded | Contact | Type: |
|---------|---------|-------|
|---------|---------|-------|

Round pin single mating end 1st contact grouping

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0