Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-331-3552

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.844 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.719 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.719 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
24

NSN 5935-00-331-3552

Electrical Receptacle Connector - Page 2 of 2



0.62	5 inches
	ninal Location:
	single mating end single contact grouping
	tact Material:
	per alloy single mating end single contact grouping
-	tact Surface Treatment:
Silve	er single mating end single contact grouping
	rt Material:
Plas	tic single mating end
	ninal Type:
Sold	er well single mating end single contact grouping
	Il Material:
Alun	ninum alloy
She	Il Surface Treatment:
Ano	dize
Incl	uded Contact Quantity:
3 sir	gle mating end single contact grouping
Incl	uded Contact Type:
Rou	nd pin single mating end single contact grouping
Prec	cious Material And Location:
Con	tact surfaces silver
Prec	cious Material And Weight:
0.00	3 silver grains, troy
Prec	cious Material:
Silve	Pr
Thre	ead Series Designator:
Une	f
She	If Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig	
A03	9b0