NSN 5935-00-331-8425

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-331-8425

| view Online at https://aerobasegroup.com/nsn/5955-00-551-6425 |
|---|
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 0.797 inches |
| Overall Diameter: |
| 0.859 inches |
| Environmental Protection: |
| Moisture resistant and vibration resistant |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 10-98 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Potting |
| Connector Locking Method: |
| Bayonet latch |
| Connector Cable Strain Relief Method: |
| Potting type |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 6 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.006 gold grains, troy and 0.006 silver grains, troy

NSN 5935-00-331-8425

Electrical Plug Connector - Page 2 of 2



| _ | | | | | |
|---|-----|-------|------|--------|---|
| μ | rac | INIIC | Mate | arıal: | • |
| | | | | | |

Gold and silver

Test Data Document:

81349-mil-c-27599 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-27599 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0