NSN 5935-00-331-8441

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-331-8441

Body Style:
Straight shape, flange mount, external coupling
Overall Height:
0.954 inches
Overall Width:
0.954 inches
Environmental Protection:
Moisture proof and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.720 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.720 inches
Distance From Mounting Shoulder To Front Face:
Between 0.317 inches and 0.322 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
10-13 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Potting type
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:

NSN 5935-00-331-8441

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

13 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.013 gold grains, troy and 0.013 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-27599 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-27599 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0