## NSN 5935-00-332-0949

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-332-0949

**Body Style:** 

Straight shape, external coupling

**Overall Height:** 

0.954 inches

**Overall Width:** 

0.954 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.719 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 

0.719 inches

**Distance From Mounting Shoulder To Front Face:** 

0.322 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

5 number 20 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

850.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Nickel alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-332-0949

Electrical Receptacle Connector - Page 2 of 2



No Fiig: A039b0