## NSN 5935-00-333-0528

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-333-0528

**Body Style:** Straight type **Overall Length:** 3.130 inches **Overall Height:** 0.585 inches **Overall Width:** 0.248 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.171 inches **Distance Between Mounting Facility Centers:** 2.840 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Polarization Method:** Mating end **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 

Contact surfaces gold

**Precious Material And Location:** 

60 single mating end single contact grouping

## NSN 5935-00-333-0528

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.060 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.