Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-333-0907

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 2.015 inches and 2.045 inches
Overall Height:
Between 1.735 inches and 1.765 inches
Overall Width:
Between 1.735 inches and 1.765 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.125 inches and 0.155 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.245 inches and 1.255 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.245 inches and 1.255 inches
Distance From Mounting Shoulder To Front Face:
Between 0.815 inches and 0.845 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
8s-1 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
20
Thread Size:
0.500 inches



Back single	mating end single contact grouping
Contact Ma	aterial:
Copper allo	y single mating end single contact grouping
Contact Su	Irface Treatment:
Tin single n	nating end single contact grouping
Insert Mate	erial:
Glass single	e mating end
Contact Su	Irface Treatment Specification:
Mil-t-10727	military specification single treatment response single mating end single contact grouping
Terminal T	ype:
Tab, solde	r lug single mating end single contact grouping
Contact Ma	aterial Specification:
Astn-b-16a	ndqq-b-626 federal specification single material response single mating end single contact grouping
Insert Mate	erial Specification:
Mil-p-18177	ormil-m-24325 military specification single material response single mating end
Included C	contact Quantity:
1 single ma	ting end single contact grouping
Included C	Contact Type:
Round pin :	single mating end single contact grouping
Thread Se	ries Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
A039b0	
Mil-std (mi	litary Standard):
Mil-t-10727	spec.