Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-333-8845

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.320 inches
Overall Height:
Between 1.302 inches and 1.323 inches
Overall Width:
Between 1.302 inches and 1.323 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inches
Distance From Mounting Shoulder To Front Face:
Between 0.604 inches and 0.609 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
18-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
18
Thread Size:
1.062 inches

NSN 5935-00-333-8845

Electrical Receptacle Connector - Page 2 of 2



Back single	mating end single contact grouping
Contact Ma	terial:
Copper alloy	single mating end single contact grouping
Contact Su	rface Treatment:
Gold single	mating end single contact grouping and silver single mating end single contact groupin
Terminal Ty	rpe:
Crimp single	mating end single contact grouping
Shell Mater	ial:
Aluminum al	loy
Shell Surface	ce Treatment:
Cadmium ar	nd chromate
Included Co	ontact Quantity:
66 single ma	ating end single contact grouping
Included Co	ontact Type:
Round pin s	ingle mating end single contact grouping
Precious M	aterial And Location:
Contact surf	aces gold and contact surfaces silver
Precious M	aterial And Weight:
0.066 gold g	rains, troy and 0.066 silver grains, troy
Precious M	aterial:
Gold and silv	ver
Thread Seri	es Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	
A039b0	