## NSN 5935-00-335-8346

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-335-8346

#### **Overall Length:**

Between 1.160 inches and 1.220 inches

#### **Overall Height:**

Between 0.880 inches and 0.940 inches

#### Overall Width:

Between 0.365 inches and 0.385 inches

#### **Environmental Protection:**

Corrosion resistant and thermal shock resistant and vibration resistant

#### **Cable Entrance Diameter:**

Between 0.133 inches and 0.143 inches

#### **Mating End Quantity:**

1

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

### **Contact Maximum Frequency Rating:**

500.0 megahertz single mating end single contact grouping

#### Shell Type:

Solid

## **Connector Cable Strain Relief Method:**

Compression nut

#### Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Silver single mating end single contact grouping

#### **Contact Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response single mating end single contact grouping

## Shell Material:

Copper alloy

#### **Shell Surface Treatment:**

Silver

#### **Shell Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response

## **Included Contact Quantity:**

1 single mating end single contact grouping

#### **Included Contact Type:**

Coaxial socket single mating end single contact grouping

## Special Features:

Dual cable openings

# **NSN 5935-00-335-8346**Electrical Plug Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surface silver
<b>Precious Material And Weight:</b>
0.001 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0