NSN 5935-00-336-2008

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-336-2008

Body Style:
Straight shape, external coupling
Overall Length:
0.672 inches
Overall Height:
0.938 inches
Overall Width:
0.938 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.719 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.719 inches
Distance From Mounting Shoulder To Front Face:
Between 0.317 inches and 0.322 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
400.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
550.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end and glass single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-00-336-2008

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and nickel Included Contact Quantity: 13 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surface gold and contact surface silver Precious Material: Gold and silver Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A039b0