

View Online at <https://aerobasegroup.com/nsn/5935-00-339-7609>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

1.588 inches

Overall Diameter:

0.946 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

10sl-4 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

2 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0