NSN 5935-00-340-9978

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-340-9978 **Body Style:** Square flange mount **Overall Length:** 2.000 inches **Bushing Diameter:** 2.062 inches **Mounting Hole Circle Radius:** 1.250 inches **Overall Diameter:** 2.875 inches **Unthreaded Mounting Hole Diameter:** 0.187 inches **Mating End Quantity: Contact Position Arrangement Style:** 3 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 30.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end all contact groupings **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Shell twistlock **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Insert Material:** Plastic phenolic single mating end **Terminal Type:** Screw single mating end all contact groupings **Shell Material:**

Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel

NSN 5935-00-340-9978

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty cfg military specification single material response single mating end

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Curved pin w/outside lip single mating end 1st contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.