Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-345-6178

## Body Style:

Straight edge type w/mounting flange

Overall Length:

1.880 inches

## **Overall Height:**

0.690 inches

Overall Width:

0.410 inches

### **Unthreaded Mounting Hole Diameter:**

0.120 inches

# Distance Between Mounting Facility Centers:

1.590 inches

## **Board Accommodated Length:**

1.100 inches single board

## **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

# Mating End Quantity:

1

### Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Criticality Code Justification:**

Feat

### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

### Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

#### **Included Contact Quantity:**

10 single mating end single contact grouping

#### **Included Contact Type:**

Leaf spring single mating end single contact grouping



#### **Special Features:**

Item must comply with requirements of desc production standard no. L01456

Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.