# NSN 5935-00-346-9344

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-346-9344

**Body Style:** 

Angle shape, pcb type

**Overall Length:** 

4.350 inches

**Overall Height:** 

0.359 inches

**Overall Width:** 

0.550 inches

#### **Environmental Protection:**

Cold resistant and heat resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

### **Unthreaded Mounting Hole Diameter:**

0.120 inches

### **Distance Between Mounting Facility Centers:**

4.100 inches

### **Mating End Quantity:**

1

### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

### **Polarization Method:**

Guide pin/socket

# **Connector Locking Method:**

Friction

### **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Side single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic polyphenylene single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Printed circuit single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# NSN 5935-00-346-9344

Electrical Receptacle Connector - Page 2 of 2



### **Guide Design And Location:**

D shape socket left-hand top at 3 oclock and d shape pin right-hand top at 3 oclock

# **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

# **Included Contact Quantity:**

70 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.070 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.