NSN 5935-00-346-9573

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-346-9573

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

Between 1.230 inches and 1.270 inches

Overall Height:

Between 0.620 inches and 0.640 inches

Overall Width:

Between 0.260 inches and 0.280 inches

Distance Between Mounting Facility Centers:

1.000 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

350.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.130 inches and 0.130 inches and 0.250 inches

Thready Qty Per Inch (tpi):

56 and 56 and 56

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact groupingcopper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and silver single mating end single contact grouping

NSN 5935-00-346-9573

Electrical Receptacle Connector - Page 2 of 2



| Insert Material: |
|--|
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 26 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Special Features: |
| Jackscrew type-male and location-left handandjackscrew type-female and location-right hand |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.026 gold grains, troy and 0.026 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unc and unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |