## NSN 5935-00-349-6941

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-349-6941

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.775 inches and 2.785 inches

**Overall Height:** 

0.542 inches

**Overall Width:** 

Between 0.307 inches and 0.317 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and salt water resistant

**Distance Between Mounting Facility Centers:** 

Between 2.440 inches and 2.450 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

36 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Special Features:** 

Printed circuit board mounting

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

## NSN 5935-00-349-6941

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.036 gold grains, troy and 0.036 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.