NSN 5935-00-350-0255

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-350-0255 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.188 inches **Overall Height:** 1.109 inches **Overall Width:** 1.109 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.437 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14s-7 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-00-350-0255

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method: |
|---|
| Externally threaded shell |
| Thread Length: |
| 0.375 inches |
| Thread Size: |
| 0.875 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Steel single mating end single contact grouping |
| Contact Surface Treatment: |
| Cadmium single mating end single contact grouping and tin single mating end single contact grouping |
| Insert Material: |
| Glass single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Steel |
| Shell Surface Treatment: |
| Cadmium and tin |
| Included Contact Quantity: |
| 3 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |
| |