## NSN 5935-00-350-6103

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-350-6103 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, round **Overall Height:** Between 1.857 inches and 1.877 inches Diameter: Between 1.580 inches and 1.590 inches **Overall Diameter:** 1.750 inches **Environmental Protection:** Corrosion resistant and humidity resistant and watertight **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Ak-9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1872.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 150.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.250 inches Thready Qty Per Inch (tpi): 12 **Thread Size:** 0.500 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-00-350-6103

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel comp 316l
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-s-365, type 2, grade a federal specification single treatment response
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Weld-on type, terminal end w/35-pitch straight knurl 1.563 in. Diameter x 0.250 in. Lg $$
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0