

View Online at <https://aerobasegroup.com/nsn/5935-00-350-6112>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Square flange mount

Overall Length:

1.590 inches

Bushing Diameter:

1.750 inches

Mounting Hole Circle Radius:

0.937 inches

Overall Diameter:

2.250 inches

Unthreaded Mounting Hole Diameter:

0.230 inches

Distance From Mounting Shoulder To Rear Face:

1.340 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nk-b9 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1872.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

90.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.270 inches

Thready Qty Per Inch (tpi):

12

Thread Size:

1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shell Material Specification:

Qq-s-763 federal specification single material response

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Furnished items - preformed packing

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0