Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-350-8192

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Overall Length:   |
| 1.281 inches  |
|   |
| Overall Height:<br>1.141 inches   |
|   |
| Overall Width:  |
| 1.281 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.120 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Height:   |
| 0.969 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.969 inches  |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping                      |
| Contact Maximum Current Rating In Amps:                                     |
| 22.0 single mating end single contact grouping                              |
| Contact Maximum Ac Voltage Rating In Volts:                                 |
| 500.0 single mating end single contact grouping                             |
| Contact Maximum Dc Voltage Rating In Volts:                                 |
| 700.0 single mating end single contact grouping                             |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Detent  |
| Thread Size:  |
| 1.000 inches  |
| Insert Material:  |
| Rubber single mating end  |
| Shell Material:   |
| Aluminum alloy  |
| Included Contact Quantity:  |
| 7 single mating end single contact grouping                                 |
| Included Contact Type:  |
| Round pin single mating end single contact grouping                         |
|   |

Electrical Receptacle Connector - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0