## NSN 5935-00-350-8193

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-350-8193

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
1.810 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.562 inches
Overall Height:
0.531 inches
Overall Width:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.343 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
42 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Contact Carrace Treatment

Gold single mating end single contact grouping

## NSN 5935-00-350-8193

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Glass single mating end and plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
42 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.042 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
N <sub>=</sub>

Fiig: A039b0