## NSN 5935-00-351-3747

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-351-3747



**Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.750 inches **Overall Diameter:** 1.812 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 19 number 16 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 4.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 24 and 24 **Thread Size:** 1.625 inches and 1.625 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Ceramic single mating end **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize

## NSN 5935-00-351-3747

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Quantity:                       |
|--|
| 19 single mating end single contact grouping     |
| Bushing Accommodation Hole Shape:                |
| Round  |
| Included Contact Type:                           |
| Banana single mating end single contact grouping |
| Thread Series Designator:                        |
| Uns and uns                                      |
| Shelf Life:                                      |
| N/a  |
| Unit Of Measure:                                 |
|  |
| Demilitarization:                                |
|  |

No Fiig: A039b0