

View Online at <https://aerobasegroup.com/nsn/5935-00-355-4093>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Length:

Between 0.687 inches and 0.751 inches

Overall Height:

Between 0.624 inches and 0.688 inches

Overall Diameter:

0.313 inches

Environmental Protection:

Shock resistant and vibration resistant and weatherproof

Cable Entrance Diameter:

Between 0.067 inches and 0.116 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sm single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 heat treated federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and silver

Shell Material Specification:

Qq-b-626 federal specification single material response or qq-b-613 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact and shell surfaces gold and contact and shell shrfaces silver

Precious Material And Weight:

0.105 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0