

View Online at <https://aerobasegroup.com/nsn/5935-00-355-6128>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.620 inches

**Bushing Diameter:**

0.210 inches

**Overall Height:**

0.500 inches

**Overall Width:**

0.500 inches

**Environmental Protection:**

Corrosion resistant and thermal shock resistant

**Unthreaded Mounting Hole Diameter:**

0.102 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.340 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.340 inches

**Distance From Mounting Shoulder To Front Face:**

0.315 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.188 inches

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530, h federal specification single material response single mating end single contact grouping

**Shell Material:**

Steel comp 303

**Shell Surface Treatment:**

Gold and nickel and copper

**Shell Material Specification:**

Qq-s-763 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Shell surface gold

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-19468 spec.