NSN 5935-00-356-7567

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-356-7567

| view Offilite at https://defobasegroup.com/nsi//0900-00-7007 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling w/backshell |
| Overall Length: |
| Between 1.303 inches and 1.353 inches |
| Overall Diameter: |
| Between 1.178 inches and 1.190 inches |
| Environmental Protection: |
| Pressure proof and moisture resistant and vibration resistant |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 18-85 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 49.0 and 169.0 and 200.0 and 244.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 1.125 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |

NSN 5935-00-356-7567Electrical Plug Connector - Page 2 of 2



| Shell Material: |
|--|
| Aluminum alloy 6061 |
| Shell Surface Treatment: |
| Chromium |
| Shell Material Specification: |
| Qq-a-367, t6 federal specification single material response |
| Included Contact Quantity: |
| 85 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material And Weight: |
| 0.085 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Un |
| Specification Data: |
| 81349-mil-c-81511/45 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |
| |
| |