NSN 5935-00-361-8881

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-361-8881

Thread Class:
2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.000 inches
Overall Diameter:
Between 1.234 inches and 1.266 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Distance From Mounting Shoulder To Front Face:
0.605 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.109 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
2
Contact Position Arrangement Style:
12-10 all mating ends
Contact Removability:
Removable all mating ends single contact grouping
Contact Maximum Current Rating In Amps:
7.5 all mating ends single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 all mating ends single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 all mating ends single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
10 and 20
Thread Size:
0.750 inches and 0.875 inches

NSN 5935-00-361-8881

Connector Adapter - Page 2 of 2



Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Rubber all mating ends

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

10 2nd mating end all contact groupings

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.002 gold grains, troy and 0.002 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Double stub and unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0