Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-365-8866

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.532 inches |
| Overall Height: |
| Between 1.615 inches and 1.635 inches |
| Overall Width: |
| Between 1.615 inches and 1.635 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| Between 0.118 inches and 0.124 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| Between 1.245 inches and 1.255 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 1.245 inches and 1.255 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.750 inches and 0.760 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 22-8 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 41.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 1250.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 1750.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| |



Connector Locking Method: Externally threaded shell **Thread Length:** 0.625 inches **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Included Contact Quantity:** 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A039b0

No