NSN 5935-00-368-2474

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-368-2474

Body Style:

Straight shape w/jackscrew

Overall Length:

Between 2.990 inches and 3.010 inches

Overall Height:

0.835 inches

Overall Width:

Between 1.070 inches and 1.090 inches

Environmental Protection:

Moisture resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

Between 2.745 inches and 2.755 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1**v**iat

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

360.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Shell Type:

Solid

Connector Locking Method:

Screw

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Stainless steel

NSN 5935-00-368-2474

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Passivate
Included Contact Quantity:
128 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Polarized in position y
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.128 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0