## NSN 5935-00-368-2877

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-368-2877 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.430 inches **Overall Height:** Between 1.850 inches and 1.870 inches **Overall Width:** Between 2.865 inches and 2.885 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.750 inches and 1.770 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.495 inches and 2.505 inches **Distance From Mounting Shoulder To Front Face:** 1.097 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Thread Length: 0.250 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-00-368-2877

Electrical Receptacle Connector - Page 2 of 2



| 14     | 11-1- | -:-1 |
|--------|-------|------|
| Insert | wate  | rıaı |

Plastic diallyl phthalate single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

## **Included Contact Quantity:**

158 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

## **Special Features:**

Polarized at position a rotated 85 deg, b rotated 137 deg

## **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unf

## **Specification Data:**

81349-mil-c-28748/09 government specification

Shelf Life:

N/a

Unit Of Measure:

\_\_

Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-m-14 spec.