NSN 5935-00-368-2878

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-368-2878 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.210 inches **Overall Height:** Between 1.850 inches and 1.870 inches **Overall Width:** Between 2.865 inches and 2.885 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.750 inches and 1.770 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.495 inches and 2.505 inches **Distance From Mounting Shoulder To Front Face:** 0.537 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Thread Length: 0.250 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Terminal Location:**

Contact Material:

Copper alloy single mating end single contact grouping

Back single mating end single contact grouping

NSN 5935-00-368-2878

Electrical Receptacle Connector - Page 2 of 2



Insert	Mate	rial

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

158 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Polarized at position a rotated 90 deg, b rotated 135 deg

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Specification Data:

81349-mil-c-28748/10 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.