

View Online at <https://aerobasegroup.com/nsn/5935-00-368-2947>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.173 inches

**Overall Height:**

Between 1.340 inches and 1.360 inches

**Overall Width:**

Between 2.410 inches and 2.430 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.240 inches and 1.260 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.040 inches and 2.050 inches

**Distance From Mounting Shoulder To Front Face:**

0.537 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Polarization Method:**

Polarization boss

**Connector Locking Method:**

Screw

**Thread Length:**

0.250 inches

**Thread Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:**

80 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Polarized at position a rotated 90 deg, b rotated 135 deg

**Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Specification Data:**

81349-mil-c-28748/10 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.