Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-368-2947

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.173 inches
Overall Height:
Between 1.340 inches and 1.360 inches
Overall Width:
Between 2.410 inches and 2.430 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.240 inches and 1.260 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.040 inches and 2.050 inches
Distance From Mounting Shoulder To Front Face:
0.537 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Polarization boss
Connector Locking Method:
Screw
Thread Length:
0.250 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Crimp single mating end single contact grouping

# Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

#### **Included Contact Quantity:**

80 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

### **Special Features:**

Polarized at position a rotated 90 deg, b rotated 135 deg

### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unf

## **Specification Data:**

81349-mil-c-28748/10 government specification

Shelf Life:

N/a

Unit Of Measure:

\_\_\_

#### **Demilitarization:**

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.